

ITA 40

STEEL STRAPPING TOOL > PNEUMATIC

Pneumatic Steel Strapping Tool with Seal for 13mm / 16mm / 19mm Steel Strap Single Notch

ITA 40 is the combined single notch pneumatic strapping tool, studied for 13mm / 16mm / 19mm steel straps.

ITA 40 is available in three motor versions (2000 N / 5500 N / 7500 N) to grant the most suitable and adjustable tension for Your application.

Lightweight and easy to be used, ITA 40 is powerful, quick and strong.

ITA 40 is manufactured to be durable and with very low maintenance required.



FEATURES

Lightweight
Strong and Reliable
Easy to be used
Low Maintenance Required
Powerful and Quick

BENEFITS

Single Notch
Adjustable Tension
Robust and durable
For a wide range of steel Straps
Suspension hook already equipped

TECHNICAL SPECIFICATION

| | |
|-------------------|--------------------|
| Dimensions | 350 x 140 x 170 mm |
| Weight | 4 Kg |

STRAP

| | |
|------------------|---|
| Type | Steel Strap - regular & high tensile |
| Width | 13mm / 16mm / 19mm |
| Thickness | 0,4mm - 0,8mm (Regular duty) 0,4mm - 0,63mm (High Tensile) |

POWER SUPPLY

| | |
|------------------------|---------------------------|
| Pressure Range | 5.5 - 7 bar (78 - 99 psi) |
| Air Consumption | 12 L/s - 25 cuft/min |

PERFORMANCE

| | |
|---------------------------|---|
| Max. tension force | 2000N / 5500N / 7500N (6 bar - 87psi) |
| Tensioning Speed | 12 mt/min (2000N) 5 mt/min (5500N) 4 mt/min (7500N) |
| Sealing | Seal Single Notch |
| Joint Strenght | 75% of breaking strenght* |

* variable according to strap type

MODEL

| CODE | DESCRIPTION |
|---------|-----------------------------|
| T401311 | ITA 40 - 13mm Steel - 2000N |
| T401321 | ITA 40 - 13mm Steel - 5500N |
| T401331 | ITA 40 - 13mm Steel - 7500N |
| T401611 | ITA 40 - 16mm Steel - 2000N |
| T401621 | ITA 40 - 16mm Steel - 5500N |
| T401631 | ITA 40 - 16mm Steel - 7500N |
| T401911 | ITA 40 - 19mm Steel - 2000N |
| T401921 | ITA 40 - 19mm Steel - 5500N |
| T401931 | ITA 40 - 19mm Steel - 7500N |